

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method to identify a potential target from image data representing a scene, comprising:
 - performing at least one of a pre-detection temporal fusion and a pre-detection spatial fusion of the image data; ~~and~~
 - thresholding the image data after performing the step of performing; and
 - identifying candidate targets from the thresholded image data.

2. (Original) The method of claim 1, wherein:
 - performing the pre-detection temporal fusion comprises temporally integrating the image data from a particular sensor across a plurality of time frames; and
 - performing the pre-detection spatial fusion comprises fusing the image data from a plurality of sensors across a single time frame.

3. (Original) The method of claim 1, wherein the pre-detection temporal fusion and the pre-detection spatial fusion includes at least one of an additive fusion, multiplicative fusion, minimum fusion, and maximum fusion.

4. (Original) The method of claim 1, wherein the thresholding includes at least one of:
 - a double-thresholding wherein an upper and a lower bound thresholds are set to identify the potential target; and

a reverse-thresholding wherein a potential target identification level is set to be below a particular threshold.

5. (Currently Amended) A method to identify a potential target from image data of a scene, comprising:

thresholding the image data, wherein said image data is image data from across multiple time frames of at least one sensor or ~~multiple image data from a plurality~~ sensor platforms; and
fusing the image data after ~~performing the thresholding; and~~
identifying candidate targets from the thresholded image data.

6. (Original) The method of claim 5, wherein thresholding includes at least one of:

double-thresholding the image data, where an upper and a lower bound threshold are set to identify the potential target; and

reverse-thresholding wherein a potential target identification level is set to be below a particular threshold.

7. (Cancelled)

8. (Original) A device to identify potential targets from image data representative of a scene, comprising:

a fusion module configured to perform at least one of integrating the image data across a plurality of time frames and integrating a plurality of images in a single time frame; and
a threshold module configured to apply thresholding techniques on the image data.

9. (Original) The device of claim 8 wherein said device further includes at least one sensor configured to sense the scene across the plurality of time frames.

10. (Original) The device of claim 8, wherein fusion module is configured to perform at least one of an additive fusion, multiplicative fusion, minimum fusion, and maximum fusion.

11. (Original) The device of claim 8, wherein the fusion module is configured to perform at least one of a pre-detection fusion and a persistence test.

12. (Original) The device of claim 8, wherein the threshold module is configured to perform at least one of a double-thresholding technique and a reverse-thresholding technique.

13. (Currently Amended) A method to identify a potential target from data, comprising the steps of:

~~providing-receiving as input data, a plurality of time frames of data~~ from at least a ~~single~~ sensor; and

performing a pre-detection technique on ~~data corresponding to~~ at least one extracted feature, where said feature is extracted from a said plurality of time frames of data ~~from the~~

~~single sensor;~~ and wherein said pre-detection technique includes either a double threshold technique or a reverse threshold technique; and
determining whether said extracted feature is a potential target.

14. (Currently Amended) A method according to claim 13 ~~which further includes the step of~~ wherein said determining includes performing a post-detection technique to determine whether a certain criteria has been met.

15. (Currently Amended) A method according to ~~claim 14~~ claim 13 wherein said pre-detection technique includes said double threshold technique, and further wherein said double-threshold technique includes setting a detection criteria having a lower bound threshold value and an upper bound threshold for determining whether an object corresponding to the extracted feature has a feature value between the lower bound threshold value and upper bound threshold value.

16. (Currently Amended) A method according to ~~claim 15~~ claim 13 wherein said pre-detection technique includes said reverse threshold technique, and further wherein said reverse threshold technique includes setting a detection criteria for a non-stationary object such that a mean value of an extracted feature is compared to a target mean value, and the extracted feature is determined to be a non-stationary object when its mean value is greater or lesser than the target mean value.

17. (Currently Amended) A method to identify a potential target from data, comprising the steps of:

~~providing-receiving, as input, data from at least a plurality of sensors; and~~
performing a pre-detection fusion technique on data corresponding to at least one extracted feature from each sensor;
wherein said pre-detection fusion technique includes at least one technique that is selected from a group comprised of additive fusion, multiplicative fusion, minimum fusion and maximum fusion; and
determining whether the pre-detection fused data is a potential target.

18. (Original) A method according to claim 17 which further includes the step of:

performing a post-detection technique when there is data from at least three sensors, said post-detection technique selected from a group consisting of a double threshold technique and a reverse threshold technique.

19. (Original) A method according to claim 18 wherein said double threshold includes setting a detection criteria having a lower bound threshold value and an upper bound threshold for determining whether an object corresponding to the extracted feature has a feature value between the lower bound threshold value and upper bound threshold value.

20. (Original) A method according to claim 18 wherein said reverse threshold technique includes setting a detection criteria for a non-stationary object such that a mean value of an

extracted feature is compared to a target mean value, and the extracted feature is determined to be a non-stationary object when its mean value is greater or lesser than the target mean value.

21. (Original) A target detection apparatus, comprising:

a plurality of sensors for outputting data related to a target, said data from each sensor having a plurality of time frames;

temporal processing means for integrating the data supplied from each of said plurality of sensors;

spatial processing means for fusing the temporally integrated sensor data from said temporal processing means, wherein said spatial processing means detects the target from the spatially fused data and provides an indication corresponding to the detected target; and

means for utilizing the indication of the detected target.

22. (New) The target detection apparatus of claim 21, the apparatus further comprising:

a threshold module that performs a pre-detection technique on at least one extracted feature, where said feature is extracted from said plurality of time frames of data of a given sensor; and wherein said pre-detection technique includes either a double threshold technique or a reverse threshold technique.